

GE

Measurement & Control



www.avionteq.com

ADTS552F

Wireless ADTS500 Series Easy-to-Use Pitot Static Tester



WiFi

Bluetooth

Swipe screen

DRUCK technology

Features

- ADTS Touch hand terminal with WiFi and Bluetooth® wireless technology (backup cable supplied)
- Accuracy suitable for RVSM validation
- 15-month calibration interval
- Swipe-action, touch screen user interface with colour graphics and menu
- 18-month calibration interval option
- Standard icons and layouts for routine testing
- Engine Pressure Ratio (EPR) option
- Multiple languages
- Stores customized aircraft test sequences
- High flow proportional pressure control technology
- Accessories bag supplied, ADTS Touch carry case option
- Large capacity pressure/vacuum pump
- Retrospectively upgradable to three or four channels
- A minimum of 5,000 pump running hours
- GE ADTS global service support
- TERPS high accuracy pressure sensors inside

Your touch, our technology



ADTS Touch

The ADTS Touch is a removable, robust wireless hand terminal that communicates to the test set via secure Bluetooth® wireless technology. This technology and the innovative design of the ADTS Touch remove the need to run cables or hoses into the cockpit.**



A rechargeable battery pack enables up to eight hours of continuous ADTS Touch wireless use. The battery can be charged by the ADTS Touch when connected to the test set, by power cable, or by an optional desk charger.

As an alternative, the ADTS Touch can be used as a conventional wired hand terminal, with or without a battery pack, by attaching a supplied cable, or as a local user interface by docking the hand terminal onto the ADTS552F.

A large, easy-to-read display in pressure or aeronautical units and swipe navigation, with intuitive icons that are logical and easy to remember, allow you to quickly scroll through available tasks. The ability to set "aircraft safety limits," enable "auto leak recovery" and save/recall aircraft test sequences make the ADTS Touch an easy-to-use hand terminal. Its multi-language selection further enhances the ADTS Touch's usability.


ADTS552F

The ADTS552F, supplied with an ADTS Touch, is a portable two-channel flightline pitot static tester with a large pitot static volume capability for use on a wide range of aircraft, from light aircraft to wide body passenger and freight aircraft.

To ensure an accuracy that is suitable for RVSM (reduced separation minimum) validation, the new ADTS552F incorporates advanced Druck TERPS (trench etched resonant pressure sensor) technology.

To satisfy the demand for a smooth rate of change into a high pitot static volume, the ADTS552F uses Druck proportional control technology coupled with a large pump capacity.

**Due to individual country radio licence requirements, Bluetooth® wireless technology may not be available in some countries. An up-to-date list of countries that the ADTS Touch with Bluetooth® wireless technology is licenced to be used in is available upon request from GE.



ADTS552F Standard Specifications

- ADTS552F pitot static tester
- ADTS Touch hand terminal
- AC power lead: 1.8 m (6 ft) length approximately
- ADTS Touch remote connecting cable: 5 m (16 ft) length approximately
- ADTS Touch battery pack
- ADTS Touch AC power supply unit
- Pack of Ps and Pt colour labels
- Multi-language installation manual
- Accessories bag
- Operator manual (installed in ADTS Touch)
- Calibration certificate traceable to international standards



ADTS552F and ADTS Touch Specifications

Parameter	Operating Range	Resolution	ADTS552F 15 mth Accuracy *	ADTS552F-E3 18 mth Accuracy *
Altitude	-3,000 to 60,000 ft	1 ft	+/-3 ft at sea level +/-7 ft at 29,000 ft +/-12 ft at 41,000 ft	+/-3 ft at sea level +/-7 ft at 29,000 ft +/-12 ft at 41,000 ft
Ps	71 to 1,130 mbar abs	0.01 mbar	+/- 0.10 mbar abs	+/- 0.10 mbar abs
Standard Airspeed (CAS)	20 to 650 knots	0.1 kt	+/-1.2 kt at 20 kts +/-0.5 kt at 50 kts	+/-1.2 kt at 20 kts +/-0.5 kt at 50 kts
Standard Airspeed Pt	71 to 1,997 mbar abs	0.01 mbar	+/- 0.10 mbar abs	+/- 0.10 mbar abs
Rate of Climb	0 to 6,000 ft/min	1 ft/min	+/- 1% Aim	+/- 1% Aim
Mach **	0 to 2.0	0.001	Better than 0.005	Better than 0.005
Engine Pressure Ratio (EPR)	0.1 to 10	0.001	Better than 0.005	Better than 0.005

* Accuracy over operating temperature includes: calibration uncertainty, non-linearity, hysteresis, repeatability, measurement stability over calibration period and control stability

**Depends on altitude at max Qc

Scaling Factors

- Altitude: ft, meters
- Airspeed: knots, km/hr, mph
- Rate of Climb: ft/min, m/min, m/s
- Others: mbar, inHg, inH2O, mmHg, kPa, hPa, psi

Rate Control/Indication

- Roc: Rate of Climb
- Rt Ps: Rate of Static
- Rt Pt: Rate of Pitot
- Rt Qc: Rate of Pt-Ps
- Rt CAS: Rate of calibrated airspeed
- Rt EPR: Rate of engine pressure ratio

Overpressure

Negligible calibration change with up to 1.25 x full scale (FS) overload applied

Calibration Stability

ADTS552F: Better than 0.05 mbar (Ps) and 0.05 mbar (Pt) over 15 months

ADTS552F-E3: Better than 0.05 mbar (Ps) and 0.05 mbar (Pt) over 18 months

Recalibration

Simple keypad instruction, use of primary standard pressure reference is recommended

Display

7" WVGA (800X480) TFT, LED backlit display. High contrast ratio, wide view angle, two readings-per-second update

Power Supplies

Auto-selection between:

100/120/230 Vac, 50/60 Hz, power - 250 VA;
115 Vac, 400 Hz, power - 250 VA

Power Failure Protection

System locks and a manual let-down feature provided

Self Test

Integral test routines and reporting for both electrical and pneumatic systems

Temperature Range

- Storage: -20°C to 70°C (-4°F to 158°F)
- Operating: 0°C to 50°C (32°F to 122°F)

Humidity

0 to 95% non-condensing

Environmental

Vibration, shock/drop and solar radiation to MIL-PRF-28800F Class 2

Conformity

EMC EN61326, LVD EN61010 (Electrical safety, PED, WEEE, CE marked)

Physical

- Weight 17 Kg (37.4 lb)
- Dimensions (including lid) H 300mm, D 425mm, W 525mm (H 11.8 in, D 16.7 in, W 20.7 in)

Pneumatic Connections

AN4 for Ps and Pt

Sealing

Weatherproof in operating mode (lid removed). Base unit IP23, ADTS Touch IP65

Pneumatic Supplies

Integral pressure and vacuum pumps capable of generating for a minimum of 5,000 running hours:

- 1,829 m/min (6,000 ft/min) into a 6L total volume (Ps 4L + Pt 2L) up to 9,144 m (30,000 ft)
- Water/moisture content vented automatically

Options and Accessories

Option - EPR Test

Engine Pressure Ratio (EPR) test (Pt/Ps for inlet/exhaust)


Option – ADTS552F-E3

ADTS552F with 18-month calibration interval (includes one UKAS calibration with new instrument)

Accessories

Part number	Description
AATOUCH-4	ADTS Touch carry case
AA500F-7	Additional ADTS Touch remote connecting cable – 5 m (16 ft) length approximately (can be connected to ADTS Touch connecting cable for 10 m (32 ft) total length)
AA500F-8	Additional ADTS Touch remote connecting cable – 18 m (59 ft) length approximately
AATOUCH-5	ADTS Touch battery pack AC desk charger (state mains lead requirement)
AATOUCH-1	Additional ADTS Touch battery pack
ADTSTOUCH	Additional ADTS Touch hand terminal (state mains lead requirement)
AA500F-1	Pressure connector AN3 male
AA500F-2	Pressure connector AN4 male
AA500F-3	Pressure connector AN6 male
AA500F-4	Pressure connector Staubli quickfit male
AA500F-5	Pressure connector Hanson quickfit male
AA500F-6	Manifold, one way + one way switched
AA500F-19	Red hose (please state length in metres or feet)
AA500F-20	Blue hose (please state length in metres or feet)
AA500F-21	Hose pressure connector AN3 female
AA500F-22	Hose pressure connector AN4 female
AA500F-23	Hose pressure connector AN6 female
AA500F-24	Hose pressure connector Staubli quickfit female
AA500F-25	Hose pressure connector Hanson quickfit female

Ordering Information



2. Options

EPR

Wireless Disabled

3. Mains Lead

Choose one from this list:

MAINS LEAD - UK PLUG

MAINS LEAD - JAPAN PLUG

MAINS LEAD - EU PLUG

MAINS LEAD - USA PLUG

MAINS LEAD - SOUTH AFRICA

MAINS LEAD - INDIA PLUG

MAINS LEAD - CHINA PLUG

MAINS LEAD - AUSTRALIA/NEW ZEALAND PLUG

MAINS LEAD - TAILS (No plug fitted)

4. Country of Use

Please state country of use for Bluetooth® wireless technology setup.**

** Due to individual country radio licence requirements, Bluetooth® wireless technology may not be available in some countries. An up-to-date list of countries that the ADTS Touch with Bluetooth® wireless technology is licenced to be used in is available upon request from GE.

5. Accessories

Please state any accessories required as separate items when placing order.

Warranty Terms

New product is supplied with an initial warranty of 24 months. For peace of mind, extend coverage on your equipment beyond the initial period up to a total four-year term.

Supporting Services

Should your equipment need calibration or maintenance, our global repair facilities are happy to serve.



www.ge-mcs.com

920-649A