

PRIME MOVER QUANTITY:

1

PRIME MOVER COOLING MEDIUM:

AIR

STAGE QUANTITY:

1

INTAKE CONNECTION QUANTITY:

1

INTAKE CONNECTION TYPE:

THREADED INTERNAL

DISCHARGE CONNECTION QUANTITY:

1

DISCHARGE CONNECTION TYPE:

THREADED INTERNAL

CURRENT TYPE:

AC

MEDIA FOR WHICH DESIGNED:

WATER, SALT

ENVIRONMENTAL PROTECTION:

SUBMERSIBLE

PUMP QUANTITY:

1

COOLING METHOD:

SELF VENTILATED

MAXIMUM DISCHARGE FLOW RATE:

180.0 GALLONS PER MINUTE

TOTAL HEAD:

50.000 FEET

OPERATING SPEED AT RATED CAPACITY:

3450.0 REVOLUTIONS PER MINUTE

PUMPING ELEMENT OPERATING POSITION:

VERTICAL

CENTRIFUGAL PUMP DESIGN:

RADIAL FLOW

CENTRIFUGAL PUMP IMPELLER QUANTITY:

1

CENTRIFUGAL PUMP IMPELLER SUCTION TYPE:

SINGLE

PRIME MOVER TYPE:

ELECTRIC MOTOR

INCLOSURE TYPE:

FULLY INCLOSED

CURRENT RATING IN AMPS:

7.5

DISCHARGE CONNECTION THREAD SIZE AND SERIES/TYPE DESIGNATOR: