

Item 3 (Ref. PD1600*)

Type P - Single phase safety, isolating and control transformer

Technical Characteristics

| | |
|----------------------|--|
| Rating: | 1600VA |
| Input Voltage: | 230/400/460V |
| Output Voltage: | 115/230V |
| Frequency: | 50/60Hz |
| Ambient temperature: | 30°C |
| Protection degree: | IP-20 |
| Cover: | Polymer of latest technology, non-flammable V-0 according to UL94 |
| Cooling: | ANAN |
| Mounting: | By screws |
| Insulation: | Class B - 130°C |
| Windings: | Class HC - 200°C |
| Protection: | Safety class I and II (selectable) |
| Test voltage: | 4,6kV (1min, 50Hz) between primary and secondary 3,2kV (1min, 50Hz) between primary and earth 2,5kV (1min, 50Hz) between secondary and earth |
| Includes: | LED indicator & metal bridges for voltage selection |
| Standards: | IEC/EN/UNE-EN 61558, CE |

Representative picture of the product



| Item | Reference* | A (mm) | B (mm) | C (mm) | D (mm) | E (mm) | ø (mm) | Weight (kg) |
|------|------------|--------|--------|--------|--------|--------|--------|-------------|
| 3 | PD1600 | 199 | 220 | 282 | 188 | 175 | 7 | 20,8 |