

WELDPLAST S2



To the product

Technical data

Voltage	200 V; 230 V	
Frequency	50/60 Hz	
Power	2400-3000 W	
Welding additive	ø 3-4 mm / 0.12-0.16 in	
Material output ø 3 mm	0.6-1.3 kg/h	1.32-2.86 lb/h
Material output ø 4 mm	1.0-2.0 kg/h	2.2-4.4 lb/h
Welding materials	HDPE; LDPE; LLDPE; PP	
Air guide	Internal	
Screw heating	Coil heater	
Air temperature control	Closed loop	
LQS	No	
Display	Yes	
Brushless blower motor	Yes	
Brushless drive motor	No	
LED Working light	No	
Length	450.0 mm	17.71 in
Width	98.0 mm	3.85 in
Height	260.0 mm	10.23 in
Weight	5.8 kg	12.78 lb
Power cable length	5.0 m	16.4 ft
Noise emission level	78 dB (A)	



WELDPLAST S2

Technical data

Approvals	CE; KC; UKCA
Protection class	I
Country of origin	CH

Scope of delivery

Welding shoe blank 45x30x54 IA; Tool case

Product items

127.215	WELDPLAST S2, 230V/3000W, EU plug
140.707	WELDPLAST S2, 230V/3000W, CN plug
146.341	WELDPLAST S2, 200V/2400W, w/o plug
156.131	WELDPLAST S2, 230V/3000W, CEE 3/16
176.839	WELDPLAST S2, 230V/3000W, CH plug