


Drivers

n°	Power Input	Power Output	LED	W	(u/h)					(%)	A (mm)	B (mm)	C (mm)	Colour	IP
1	FL FLC1524VT	230	24V/DC	LED	15	30000	-	-	-	YES	121	45	16	WHITE	20
2	FL FLC3024VT	230	24V/DC	LED	30	30000	-	-	-	YES	150	60	32	WHITE	20
3	FL FLC7524VT	230	24V/DC	LED	75	30000	-	-	-	YES	180	60	32	WHITE	20
4	FL FLC20024VT	230	24V/DC	LED	200	30000	-	-	-	YES	250	65	38	SILVER	66

Omgevingstemp. /Temp. ambiente - 30 °C > + 40 °C



- Short circuit, over current and over voltage protection. Up to 80% efficient.
- Fireproof environmental protection PC plastic cover

Driver

n°	Power Input	Power Output	LED	W	(u/h)					(%)	A (mm)	B (mm)	C (mm)	Colour	IP
1	BC DR6024PD	240	24V/DC	LED	60	50000	-	-	-	YES	190	65	29	GREY	20
1	BC DR8024PD	240	24V/DC	LED	80	50000	-	-	-	YES	190	65	29	GREY	20

Omgevingstemp. /Temp. ambiente - 30 °C > + 45 °C

